



# Material Safety Data Sheet

Product Name: **ISOFLEX NBU 15**  
Article Number: **004026**  
Date: April 21, 2009  
Replaces: August 7, 2007  
Page: 1 of 3

---

## Section 1 – Company Identification

Klüber Lubrication North America L.P.  
32 Industrial Dr.  
Londonderry, NH 03053  
Phone: (603)647-4104

**Emergency Phone**  
United States (800)424-9300 (ChemTrec)  
International (703)527-3887

---

## Section 2 – Composition Information

Barium complex soap  
Mineral oil  
Synthetic hydrocarbon oil  
Ester oil

---

## Section 3 – Health Effects

**Eyes:** May cause irritation upon contact.

**Skin:** May cause irritation upon repeated contact.

**Inhalation:** Vapor inhalation under ambient conditions will not occur, however, if heated to high temperatures, oil mist may cause irritation to the respiratory tract.

**Ingestion:** May cause irritation to respiratory tract and diarrhea.

---

## Section 4 – First Aid Measures

**Eyes:** Flush eyes with clean water for 20 minutes. Seek medical attention if irritation persists.

**Skin:** Wash with soap and water. Seek medical attention if irritation or rash persists.

**Inhalation:** Remove victim to fresh air. If respiratory problems continue, seek medical attention.

**Ingestion:** Wash out mouth immediately. Do not induce vomiting. Seek medical attention.

**Advice to Physician:** Treat systematically.

---

## Section 5 – Exposure Controls

**Eye Protection:** Safety goggles or safety glasses with side shields when applying product to moving parts. Consult your company's policy regarding eye protection.

**Hand Protection:** Protective gloves are recommended. Consult your company's policy regarding hand protection.

**Body Protection:** Clean overalls. Consult your company's policy regarding personal protective clothing.

**Respiratory Protection:** During normal use, no special respiratory protection is required, however, if misting / vapors occur due to high heat or fire, use self contained breathing apparatus that has a full face piece and is operated in a pressure-demand or other positive-demand mode. Consult your company's respiratory protection policy.

	TLV	PEL
Mineral oil	5 mg/m <sup>3</sup> (oil mist)	5 mg/m <sup>3</sup> (oil mist)

The information herein is given in good faith, but without warranty, express or implied. All risks of use of the product are therefore assumed by the user. Appropriate warnings and safe handling procedures must be provided to handlers and users.



# Material Safety Data Sheet

Product Name: **ISOFLEX NBU 15**  
Article Number: **004026**  
Date: April 21, 2009  
Replaces: August 7, 2007  
Page: 2 of 3

---

**Other Protective Measures:** Emergency eyewash / shower equipment should be readily available.

---

## Section 6 – Fire Fighting Measures

**Flash Point:** May be combustible at high temperatures.

**Lower Explosion Limit:** Not determined.

**Upper Explosion Limit:** Not determined.

**Extinguishing Media:** Water mist, foam, dry chemical or carbon dioxide. Do not use water jet as this may spread fire and contamination. Product may float and re-ignite.

**Respiratory Protection:** Self contained breathing apparatus that has a full face piece and is operated in a pressure-demand or other positive-demand mode.

---

## Section 7 – Accidental Release

If product leaks or is inadvertently spilled, eliminate ignition sources and prevent spill from entering drains and waterways. Absorb spilled product with absorbent and place in a container for proper disposal.

---

## Section 8 – Handling and Storage

**Handling:** No special handling precautions are required, however, good personal hygiene is recommended. Wash hands with soap and water after use and before eating, drinking or smoking. Use product in well ventilated areas.

**Storage:** Keep container tightly closed in a cool, well ventilated place. Keep away from foodstuffs. Keep away from elevated temperatures. Keep away from children.

---

## Section 9 – Physical and Chemical Properties

**Appearance:** Beige grease.

**Drop Point:** > 220° C.

**Vapor Pressure (mm Hg):** Not determined.

**Density:** ~ 0.99 g/cm<sup>3</sup> @ 20° C.

**Solubility in Water:** Insoluble.

---

## Section 10 – Stability and Reactivity

**Stability:** Stable under ambient conditions.

**Conditions to Avoid:** Open flames and heat sources.

**Materials to Avoid:** Oxidizing agents.

**Hazardous Decomposition Products:** Burning generates smoke, carbon monoxide, carbon dioxide, and airborne soot.



# Material Safety Data Sheet

Product Name: **ISOFLEX NBU 15**  
Article Number: **004026**  
Date: April 21, 2009  
Replaces: August 7, 2007  
Page: 3 of 3

---

**Hazardous Polymerization:** Will not occur.

---

## Section 11 – Toxicological Information

**Acute Toxicity:** Not determined.  
**Chronic Toxicity:** Not determined.  
**Sensitization:** Not known to be a sensitizer.

---

## Section 12 – Disposal Considerations

Under RCRA, it is the responsibility of the user, at the time of disposal, to determine whether the product meets the RCRA criteria for hazardous waste. As a new product, it is considered a RCRA hazardous waste.  
TCLP: 345 mg/L Barium.  
Waste code: D005.

---

## Section 13 – Transportation

**DOT:** Not regulated.

---

## Section 14 – Regulatory Information

**TSCA Section 8(b) Inventory Status:** All components are either exempt or listed on the TSCA inventory.  
**TSCA Section 12(b) Export Notification:** This product does not contain any component(s) that are subject to Section 12(b) Export Notification.  
**EPCRA Section 302 Extremely Hazardous Substance (EHS):** This product does not contain any component(s) regulated under Section 302 (40 CFR 355) as Extremely Hazardous Substances.  
**EPCRA Section 304 CERCLA Hazardous Substance:** This product does not contain any component(s) regulated under Section 304 (40 CFR 302) as hazardous chemicals for emergency release notification.  
**EPCRA Section 313 Toxic Chemical List:** Barium compound (30 – 40%).  
**WHMIS:** Not controlled.  
**RoHS:** Compliant.

---

## Section 15 – Additional Information

HMIS Rating

Health: 1

Flammability: 1

Reactivity: 0

Personal Protection: B